

SCM

ACCESSORY FOR SCMLCDN+1

MODEL **SCM-AES/EBU**



ORDERING INFORMATION

Model	Description
SCM-AES/EBU	Passive AES/EBU audio signal switch unit for SCMLCDN+1 changeover.



SCM-AES/EBU

Accessory for SCMLCDN+1.

FEATURES

PRIMARY APPLICATION: this device is specifically used for changeover between digital audio signals that supports AES/EBU in conjunction to SCMLCDN+1 changeover system, even in presence of an analog audio changeover such as the SCM-AUD.

HARDWARE FEATURES: the system housed in lightweight and rugged stainless steel rack cases having the dimension of 3 HE.

USER-FRIENDLY FEATURES: the front panel features one led that indicate instant system status to the operator.

EASE OF MAINTENANCE: all RVR changeover systems are assembled using modules and boards with connectors so that it is easy to remove, replace and add modules and boards.

INTERFACE CONTROL: the rear panel features all connectors that could be used to connect the equipment to the various station components.

- Changeover unit between digital audio signals that supports AES/EBU in conjunction to the SCMLCDN+1 changeover system.
- Can be integrated to the SCMLCDN+1 even in presence of the SCM-AUD analog audio changeover.
- Lightweight and rugged stainless steel 1 HE rack case.

SCM-AES/EBU

Parameters		Value	Notes
GENERALS			
Ambient working temperature		-10 °C to + 50 °C / 95%	Relative humidity non condensing
POWER REQUIREMENTS			
AC Power input	AC Supply Voltage	80 - 260 VAC	Full Range Monophase
	Active Power Consumption	1W	
	Connector	VDE IEC Standard	
MECHANICAL DIMENSIONS			
Physical dimensions	L x H x W	mm / inch	483 / 19
		mm / inch	44 / 3 1/2
Weight		kg	About 1,4
Cooling			Convection cooling
Acoustic noise		dBA	0
AUDIO INPUTS			
L&R (from 1 to 4)	Connector		XLR female Balanced
	Data Formats		AES/EBU
	Impedance		110 Ω
OUTPUTS			
AES/EBU (from 1 to 4) & Reserve	Connector		XLR male Balanced
	Data Formats		AES/EBU
	Impedance		110 Ω
INTERFACES			
Signalling LED			Yes
COMMAND	IN		DB25 Female (SCMLCDN+1 or SCM-AUD interface)
FUSES			
On mains			1 External fuse F 315 mA - 5X20 mm

All pictures are RVR's property and they are only indicative and not binding. The pictures can be modified without notice. These are general specifications. They show typical values and are subject to change without notice.



R.V.R. Elettronica S.r.l.
Via del Fonditore 2/2 c
40138 Bologna - Italy
Phone +39 051 6010506
info@rvr.it

www.rvr.it