

# Audio & RDS Equipments

> *audio Distributor Systems*

**AUD5DSTB**



AUD5DSTB front view

## Features

- > **PRIMARY APPLICATION:** the audio distribution system allows you to split the audio signal in input and redistribute it on multiple outputs.
- > **TECHNICAL FEATURES:** the stereo, or mono, signal is distributed

actively on 5-way.

- > **HARDWARE FEATURES:** the audio distribution system housed in lightweight and rugged stainless steel rack cases having the dimension of 1 HE.

## Caratteristiche

- > **PRIMARY APPLICATION:** il sistema di distribuzione audio permette di dividere il segnale audio in ingresso e ridistribuirlo su più uscite.
- > **TECHNICAL FEATURES:** il segnale stereo, o mono, viene distri-

buito in modo attivo su 5 vie.

- > **HARDWARE FEATURES:** il sistema di scambio è realizzato in contenitore rack in acciaio inox incredibilmente leggero e robusto in dimensioni di 1 HE.

# Audio & RDS Equipments

BROADCAST  
EQUIPMENT

## Technical specifications

Parameter		AUD5DSTB	Value
<b>GENERALS</b>			
Physical Dimensions	L x H x W		436 x 41 x 239 mm
Overall Dimensions	L x H x W		483 x 44 x 252,6 mm
Weight			2,5 kg
Operating Temperature			From -10 °C to + 50 °C
Operating Humidity			95% non condensing
<b>POWER REQUIREMENTS</b>			
AC Power Input	AC Supply Voltage		115 / 230 VAC ±15%, internally selectable
	Active Power Consumption		2 W
	Connector		VDE IEC Standard
<b>INPUTS</b>			
Left & Right	Connector		XLR balanced (female)
	Impedance		600 Ω / 10kΩ
	Bandwidth		From DC to 20kHz
<b>OUTPUTS</b>			
Left & Right	Connector		5x XLR balanced (male)
	Impedance		< 100 Ω
	Channels gain		0 db
	Bandwidth		From DC to 20kHz
<b>FUSES</b>			
On Mains			2 External fuse F 1A - 5X20 mm

All pictures are RVR's property and they are only indicative and not binding. The pictures can be modified without notice.  
These are general specifications. They show typical values and are subject to change without notice.

CE 99/5/CE Revision: 05/15

audio &  
RDS equipments